

QUINN ROOFTILES

RATHMORE MOCK BOND

Quinn Rooftiles are manufactured to the latest European standard BS EN 490. Every Tile produced carries with it the Kitemark seal of approval that confirms our products outstanding quality and appeal. Quinn Rooftiles have sustained investment to manufacture Rooftiles of outstanding quality, character and style.

Description

MOCK BOND RATHMORE ROOF TILE offers you the perfect combination of an attractive slate like appearance at an equally attractive price. The extremely thin, clean and precise slate like appearance is enhanced by the thin leading edge which is sculpted to imitate the riven edges of natural slate. The mock bond centre line further enhances the look by giving the impression of two smaller slate sized units being used.



Packaging

No. of tiles/pallet - 240

Technical Properties

Size	420mm x 334mm
Minimum Pitch	17.5°
Maximum Pitch (without special fixing)	44°
Headlap (min/max)	17.5° - 22.5° 100mm (min) 140mm (max)
	above 22.5° 75mm (min) 140mm (max)
Maximum Gauge	345mm
Linear cover	300mm - 302mm
Covering Capacity (nett at 320mm gauge)	10.4 Tiles/m ²
Surface	Smooth
Weight (approx.)	at 320 gauge 48kg/m ²
Weight (approx.)	4.6 tonnes per (1,000 tiles)
Batten size* (Rafter centres not exceeding 600mm)	50mm x 36mm 38mm x 25mm
Battens required (nett)	3.1 metre/m ² (at 320mm gauge)

Abutment	Secret Gutter (cover Flashing)
Eaves	Standard Tile
Ridge/Hip	457mm angle type, Ridge Tile butt-jointed
Valley	Open metal valley / Open trough valley lead lining (or other approved lining)

* Note: Refer to National Standard

KBM

KEITH BUILDERS MERCHANTS LTD

ROOF TILES

**CONCRETE ROOF TILES
AVAILABLE FROM STOCK NOW**



**QUINN ROOFING SYSTEM
GUARANTEE**



**Call Keith 01542 886222
or Forres 01309 676444 for details**